



BOSS

LUBRICANTS



BOSS GEAR OIL LUBRICANTS

PRODUCT DESCRIPTION AND BENEFITS

- Petroleum base gear oils meeting the performance requirements of the API Service designation GL-5, the MACK GO-H and the MIL-L-2105 specification
- Multi-purpose oils, recommended for manual transmissions, automotive and truck differentials, driving rear axles and limited slip applications
- Formulated with a high performance sulfur-phosphorous additive system and high quality paraffinic base stock to ensure excellent field performance
- Provide outstanding thermal stability, excellent corrosion protection and superior seal compatibility

PERFORMANCE SPECIFICATION

SAE GRADE	75W90	80W90	85W140
Gravity, °API	29.3	28.1	25.5
Density @ 15°C, Kg/l	0.8801	0.8866	0.9013
Viscosity, cSt @ 40°C	112.8	139.4	318.9
Viscosity, cSt @ 100°C	14.25	14.83	25.46
Viscosity Index	124	107	99
Brookfield Viscosity	150,000 (-40°C)	105,000 (-26°C)	36,400 (-12°C)
Flash Point, °C	213(coc)	216(coc)	185(PMCC)
Pour Point, °C	-42	-33	-24

CANADIAN OWNED, CANADIAN MADE, FOR CANADIAN CLIMATES.

QUALITY, VALUE, SERVICE AND SUPPORT

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of its products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457 or fax (403) 279-2272 #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

WWW.BOSSLUBRICANTS.COM

1 | Page