

BOSS FIFTH WHEEL GREASE

PRODUCT DESCRIPTION AND BENEFITS

- Designed primarily for fifth wheel applications only
- Formulated with corrosion, oxidation and anti-wear additives to ensure excellent plate protection
- A tacky frictional modifier has been incorporated in this formulation to ensure excellent adhesiveness
- NLGI certified LB

•

NOTE: For initial greasing, the fifth wheel should be cleaned thoroughly to ensure that the fifth wheel grease will adhere properly

PERFORMANCE SPECIFICATIONS

GRADE NLGI	2
Penetration Range @ 25C	
ASTM Worked	265-295
Dropping Point	
ASTM, C	174 C
Soap Type	Lithium 12 Hydroxy Stearate
Color	Blue
Appearance	Butter and Tacky

^{*}Values shown here are typical and may vary

CANADIAN OWNED, CANADIAN MADE, FOR CANADIAN CLIMATES. QUALITY, VALUE, SERVICE AND SUPPORT

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of its products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457 or fax (403) 279-2272 #112, 6303 30th Street S.E. Calgary, AB T2C 1R4 WWW.BOSSLUBRICANTS.COM



