



BOSS

LUBRICANTS



BOSS ZRX 4- STROKE MOTORCYCLE OILS

PRODUCT DESCRIPTION AND BENEFITS

- Formulated to meet the special engineering requirements of the motorcycle wet clutch systems
- Carefully balanced premium additive system that will give outstanding deposit control, minimize sludge and varnish, and control wear under the most severe service condition
- Multi-viscosity formulas offer superior high temperature protection along with easier starting and a rapid oil flow

PERFORMANCE SPECIFICATION

SAE VISCOSITY GRADE	10W40	20W50
Density @ 15.6°C, Kg/L	0.8866	0.8927
Viscosity, cST @ 40°C	95.7	171
Viscosity, cST @ 100°C	13.4	19.0
Viscosity Index	140	126
CCS Viscosity, cP @ -10°C	3300	4200
Flash Point, °C	204	226.7
Pour Point, °C	-31.7	-26.1
Sulphated Ash, Mass %	1.10	1.15
Filter Ability Test (GM EOFs)	Pass	Pass
Foam Test (D-892)	Pass	Pass

PROPERTIES

- Exceeds API Service Categories SL/SJ/CD/CF
- Meets and exceeds performance requirements of BMW, HARLEY DAVIDSON, HONDA AND KAWASAKI

CANADIAN OWNED, CANADIAN MADE, FOR CANADIAN CLIMATES.

QUALITY, VALUE, SERVICE AND SUPPORT

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of its products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457 or fax (403) 279-2272 #112, 6303 30th Street S.E. Calgary, AB T2C 1R4
WWW.BOSSLUBRICANTS.COM*



INDEPENDENT LUBRICANT
MANUFACTURERS ASSOCIATION



