



BOSS

LUBRICANTS



BOSS ATF FLUID (DEXRON III MERCON)

PRODUCT DESCRIPTION AND BENEFITS

- The latest high performance multipurpose power transmission fluid approved under DEXRON®-III and MERCON specifications.
- Manufactured using highly refined paraffinic base oils, a shear stable V.I. improver and additive systems that provide oxidation and thermal stability, friction control, corrosion and wear protection.
- Will prevent the accumulation of deposits and the formation of sludge, varnish and foam.
- SUPERIOR COLD TEMPERATURE CHARACTERISTICS.
- EXCELLENT WEAR PROTECTION.
- SEAL COMPATIBILITY.
- SUPERIOR FRICTIONAL CHARACTERISTICS.
- RUST AND CORROSION PROTECTION.
- EXCELLENT OXIDATION RESISTANCE AND FOAM PROTECTION.

PERFORMANCE SPECIFICATIONS

TYPICAL TEST PROPERTIES

Density at 15°C, kg/l	.8550
Viscosity, cSt @40°C	37.0
Viscosity, cSt @ 100°C	7.3
Brookfield Viscosity cP @ -20°C	1,000
-40°C	17,000
Viscosity Index	173
Flash Point, °C	177
Pour Point, °C	-48
Colour	RED



INDEPENDENT LUBRICANT
MANUFACTURERS ASSOCIATION



APPLICATIONS

This product meets the licensing and performance requirements of:

- GM DEXRON®-III DEXRON®-II DEXRON-G – 34447
- FORD MERCON®-M - 980508
- ALLISON C -4 Approval Number C4-25573197

*** This product is suitable in any transmission where the manufacturer recommends a DEXRON III or MERCON qualified product.**

**CANADIAN OWNED, CANADIAN MADE, FOR CANADIAN CLIMATES.
QUALITY, VALUE, SERVICE AND SUPPORT**

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of its products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457 or fax (403) 279-2272 #112, 6303 30th Street S.E. Calgary, AB T2C 1R4
WWW.BOSSLUBRICANTS.COM*



INDEPENDENT LUBRICANT
MANUFACTURERS ASSOCIATION

