



PRODUCT SPECIFICATION DATA SHEET



BOSS ROCK DRILL LUBRICANT

CUSTOMER BENEFITS:

BOSS ROCK DRILL LUBRICANTS are an adhesive extreme pressure lubricant specifically designed for use in air-powered tools such as rock drills, pavement breakers, stoppers, drifters, tampers, riveters and impact tools.

PERFORMANCE SPECIFICATIONS:

ISO Grades	22	68	100
Viscosity, CST @ 40°C	22.1	68.1	100.1
Viscosity, CST @ 100°C	4.6	9.3	11.8
Viscosity Index	128	113	109
Pour Point, °C	-45	-27	-24
Timken Ok Load, Kg	25	25	25
Flash Point, °C	166	201	206
Color	Dark Brown	Dark Brown	Dark Brown

Ambient Temperature	ISO Grade
10°C to 32°C	100
-15°C to 10°C	68
-35°C to -15°C	22

APPLICATIONS:

BOSS RD 22 is a low viscosity lubricant for cold temperatures and winter conditions
BOSS RD 68 & 100 are popular viscosity grades for use extensively for a wide range of operating conditions and equipment.

PROPERTIES:

Extreme pressure properties for protection against shock loading and seizure
Protection against wear
Good adhesiveness to metal surfaces in the presence of moisture
Protects against corrosion caused by moisture and rusting