

BOSS MAXX Life Antifreeze

PRODUCT DESCRIPTION AND BENEFITS

- Fully formulated, pre-charged extended life antifreeze
- Developed specifically to meet the stringent specifications for the new "Global Extended Life" category of antifreezes

PERFORMANCE SPECIFICATION

As Concentrated Antifreeze (made with Ethylene Glycol)

Specific Gravity 1.120-1.125

pH 9.0-10.5 (7.0-11.0)

Reserve Alkalinity 6 ml min. Freeze Point -34°F max

(diluted to 50% w/ Water)

APPLICATIONS

- Suitable for passenger cars, vans, SUV's, light trucks, and heavy duty vehicles.
- Outstanding aluminum corrosion control in addition to superior protection for copper, brass, solder, steel, and cast iron.
- In heavy duty applications, it will have a service life of 600,000 miles with the addition of an additive booster at 300,000 miles.
- Should be checked at every oil change to be sure the pH is in the proper range and that the sample is free of significant precipitates, suspended solids, cloudiness or contamination





PROPERTIES

BOSS MAXX Life Antifreeze meets the following specifications:

- ASTM D 3306
- ASTM D 4985
- ASTM D 6210/6211
- TMC of ATA RP392/338
- BS 6580
- Chrysler MS 7170
- Chrysler MS 9769
- Ford ESE M97B44-A
- Ford WSS M97B44-D
- Ford WSS M97B51-A1
- ANFOR R15-601
- GM 1825M
- GM 6277M (DEX-COOL)
- JASO M325
- Mercedes Benz DBL 7700

Nearly all the OEM automotive light-duty and heavy-duty specifications are patterned after of identical to the ASTM standard specifications given above. Note that the ASTM Specifications listed include the key performance tests (ASTM D1384,D4340,D1881,D2570,D2809)

CANADIAN OWNED, CANADIAN MADE, FOR CANADIAN CLIMATES. QUALITY, VALUE, SERVICE AND SUPPORT

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of its products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457 or fax (403) 279-2272 #112, 6303 30th Street S.E. Calgary, AB T2C 1R4 WWW.BOSSLUBRICANTS.COM



