



PRODUCT SPECIFICATION DATA SHEET



BOSS UNIVERSAL TRACTOR FLUIDS

Customer Benefits:

BOSS UNIVERSAL TRACTOR FLUIDS (UTF) are high quality transmission / differential / hydraulic fluids recommended for use in power shifts / hydrostatic / manual transmissions, differentials, final drives, wet brakes / clutches, PTO drives commonly utilized in farm and construction equipment, off highway vehicles and industrial tractors.

PERFORMANCE SPECIFICATIONS:

Density, kg/m ³ @ 15°C	0.869
Kinematic Viscosity	58.7
Viscosity cST@100c	9.4
Viscosity Index	140
Flash Point (COC), °C	226
Pour Point, °C	-42
Colour (ASTM)	3.0
Brookfield Viscosity	2600

Applications:

Allison: C-3/C-4 or CAT TO-2

John Deere: J20A, J20C

J.I Case: MS1209

Ford New Holland: M2C -41B, -48B, -48C, -86C, 134D, MAT 3525

Kubota: B6 (UDT)

Vickers: 35VQ25

Properties:

- Minimizes wet brakes and clutch chatter for vibration free operation.
- Compatible with seal materials used for the applications recommended.
- Excellent EP properties to reduce gear pitting and wear.
- Excellent anti-wear properties for longer bearing and hydraulic pump life.
- Provides a wide temperature operating for summer and all but the most severe winter operations.
- Viscosity range equivalent to a 5W30 engine oil.
- Good corrosion protection even in presence of moisture.
- Power shift transmission specifying long fluid life due to its excellent oxidative fluids.
- Good filterability.