

A fast tacking adhesive for lightweight material such as leather, fabric or plastics. It can also be used as an adhesive for bonding engine gaskets.

APPLICATION:

Surface must be free of wax, silicone, grease, dirt and other contaminants.

1. Wash surface with soap and water.
2. Clean metal surfaces with PF 605 Wax and Grease Remover, plastic surfaces with PF 606 Plastic Parts Cleaner. Wipe dry while the surface is still wet.
3. Shake can for 1 minute after mixing ball moves freely.
4. For best results, use only when temperature of material and surfaces are between 70°F and 75°F (21°C and 24°C).
5. Spray can approximately 6 to 8 inches (15 to 20 cm) from surface.
6. Spray both surfaces to be joined, align and press firmly together. Allow 2 to 4 minutes drying time.
7. When finished, turn can upside down and spray about 3 seconds to clean out spray head.

CAUTION: Solvent in the product may mar or attack some automotive paint and plastic surfaces. Masking is recommended where overspray may occur. Do not use on unsupported flexible vinyl. This product is not recommended for installation of complete or partial vinyl tops.

TECHNICAL DATA:

APPEARANCE:	YELLOW
ODOUR	HYDROCARBON ODOUR
FLASH POINT:	-28.9C (HEXANE); FLAME PROJECTION >45 CM < 100CM
VOC:	376 g/L 3.14 lbs/USG

PRECAUTIONARY INFORMATION

Refer to product label and Safety Data Sheet for health and safety information before using this product.

SAFETY CONSIDERATION

Safety Data Sheets are available at www.proformproducts.com or upon request at info@proformproducts.com. These are provided to help our customers satisfy their own handling, safety and disposal needs, and those required by local applicable health and safety regulations. Our Safety data sheets are updated regularly, therefore, please review the most current Safety Data Sheet before handling or using any product.

TECHNICAL INFORMATION:

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Pro Form believes are reliable, but the accuracy or completeness of such information is not guaranteed.



Product Data Sheet

Sprayable Adhesive

PF 505

PRODUCT USE:

Many factors beyond Pro Form's control and uniquely within user's knowledge and control can affect the use and performance of a Pro Form product in a particular application. Given the variety of factors that can affect the use and performance of a Pro Form product, user is solely responsible for evaluating the Pro Form product and determining whether it is fit for a particular purpose and suitable for user's method of application.

WARRANTY, LIMITED REMEDY, DISCLAIMER AND LIMITATION OF LIABILITY

Pro Form Products Ltd. ("Pro Form") makes no warranty, either express or implied, and specifically excludes any implied warranties or conditions of quality, whether of merchantability, fitness or otherwise. On any claim, irrespective of the legal theory invoked, Pro Form's total liability shall not exceed the purchase price of the product. At its option, Pro Form may instead replace or repair the product. In no event shall Pro Form be liable for any damages of any type, or for loss.