



BOSS HIGH PERFORMANCE GASOLINE

ENGINE OILS 5000 SERIES

PRODUCT DESCRIPTION AND BENEFITS

- Formulated for turbo-charged and naturally aspirated gasoline, propane, and natural gas engines in passenger car and light duty truck service
- Exceed API service SN and previous service categories, as well as the requirements of ILSAC starburst GF-5

PERFORMANCE SPECIFICATION

SAE GRADE	5W20	5W30	10W30	10W40*	20W50*
DENSITY, (D4052), kg/m@ 15C	863	863	872	876	886
Kinematic Viscosity (D445) cST @ 40C	49.7	623.2	69.5	103.3	165
cST @ 100C	8.6	10.6	10.6	11.5	18.1
Viscosity Index (D2270)	150	155	140	151	120
CCS Viscosity (D2602) cP @ -30 C	6100	6300	-	---	---
cP @ -25 C	---	---	6300	6400	---
Flash Point (D92), C	218	224	234	236	256
Pour Point (D97), C	-42	-42	-36	-33	-30
Color (ASTM)	3.0	3.0	3.5	3.5	3.5
Ash Sulphated, mass%	0.92	0.92	0.92	0.92	0.92

Note: Values shown above are representative of current production and may vary within modest ranges

APPLICATIONS

- Passenger car and truck gasoline. Engines specifying API service SN, SM, SL, SJ, SH, SG, SF engine oils
- Passenger car and truck propane and natural gas engines
- Maintains the warranty requirements for today's passenger car and truck light duty trucks specifying ILSAC Starburst GF-1, GF-2, GF-3, GF-4, and GF-5 engines



INDEPENDENT LUBRICANT
MANUFACTURERS ASSOCIATION





- Lubricates, cools, and protects turbo-charged high-revving engines that operate at high temperatures
- Protects the engine in controlling varnish, deposits, rust, corrosion, wear and cleanliness

CANADIAN OWNED, CANADIAN MADE, FOR CANADIAN CLIMATES.

QUALITY, VALUE, SERVICE AND SUPPORT

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of its products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457 or fax (403) 279-2272 #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

WWW.BOSSLUBRICANTS.COM



INDEPENDENT LUBRICANT
MANUFACTURERS ASSOCIATION

